

TAB Motion Pasted

is a flooded small traction battery with flat grid plates.

ADVANTAGES:

- + excellent vibration resistance,
- + high rate discharge capability,
- + high performance in difficult working conditions,
- + economical and reliable ...

APPLICATIONS:

- + wheelchairs,
- + truck applications,
- + caravans and motorhomes,
- + battery driven carts,
- + boats,
- + cleaning machines,
- + solar systems ...

CHARGING:

- + TAB Motion batteries can be recharged with 50 Hz or HF charger.
The charging profile is Wa; WoWa, IUla; WUIa acc. to DIN 41773 and 41774.



TAB Motion Pasted

Number of cycles: 300 (IEC / EN 60254-1 / 25 °C)

| TAB ID | Short code | C100 (Ah) | C20 (Ah) | C5 (Ah) | Box Type | Voltage (V) | L×W×H (mm) | BHD | Layout | PCS per Pallet (EUR/CNT) | Weight (kg) |
|--------|------------|-----------|----------|---------|----------|-------------|-----------------|-----|--------|--------------------------|-------------|
| 207860 | 50 P | 70 | 60 | 50 | L2 | 12 | 242×175×190 | B13 | 0 | 57/90 | 16,4 |
| 207875 | 60 P | 80 | 75 | 60 | L3 | 12 | 278×175×190 | B13 | 0 | 48/80 | 19,0 |
| 207905 | 85 P | 115 | 105 | 85 | L5 | 12 | 353×175×190 | B13 | 0 | 36/60 | 23,7 |
| 206895 | 80 P | 115 | 105 | 80 | 59518 | 12 | 312×176×212 | B0 | 0 | 36/60 | 22,3 |
| 205105 | 105 P | 125 | 120 | 105 | 60528 | 12 | 344×172×212/234 | B0 | 0 | 36/48 | 26,7 |
| 206125 | 110 P | 155 | 140 | 110 | 62512 | 12 | 344×172×262/284 | B0 | 0 | 24/36 | 31,8 |
| 205835 | 110 P MAC | 150 | 140 | 110 | MAC 110 | 12 | 509×175×182/208 | B0 | 3 | 24/40 | 34,3 |
| 205880 | 150 P | 190 | 180 | 150 | B | 12 | 512×222×194/221 | B0 | 3 | 21/28 | 43,7 |
| 205925 | 190 P | 245 | 225 | 190 | C | 12 | 518×273×214/240 | B0 | 3 | 18/24 | 56,1 |